



PRODUCT MANUAL

RECCE PRO[®] HD

8x32 MONOCULAR

SPECIFICATIONS

MAGNIFICATION x OBJECTIVE LENS DIAMETER	8x32
LINEAR FIELD OF VIEW (@1000 YDS.)	400'
ANGULAR FIELD OF VIEW	7.6°
CLOSE FOCUS	5.0'
EYE RELIEF	14.5mm
DIOPTRER RANGE	±3
EYECUP STYLE	Winged
LENGTH	6.0"
WEIGHT	10.5 oz.

Images are for representation only.
Product may vary slightly from what is shown.

RECCE PRO® HD MONOCULAR

Made for tactical shooters and military professionals, the RECCE Pro® HD delivers high-definition clarity and rapid range estimation with its MRAD milling reticle. Compact, lightweight, and built to deploy fast, it's always within reach—helping you lock onto your target quickly and reliably when every shot counts.



BASIC OPERATION

Adjust the Eyecup

The heavy-duty Winged Eyecup folds up and down for optimal viewing with or without eyeglasses. If you are viewing with eyeglasses, fold the Eyecup down for best viewing. The Eyecup will rotate to accommodate use with either your left or right eye.



Adjust Eyecup for best viewing

Adjust the Image Focus

To adjust the image focus, rotate the Image Focus Wheel until the image is in focus.


Adjust the Reticle Focus

The Reticle Focus Wheel adjusts the sharpness of the reticle. While looking at a blank wall or blue sky, rotate the Reticle Focus Wheel until the reticle is in focus.




USING THE R/T RANGING RETICLE

The R/T Ranging reticle is based on an angular measurement called the milliradian (MRAD) which allows you to calculate ranges when comparing the reticle to an object of a known dimension. The key to effective ranging with this reticle is knowing the measurements of common objects in your vicinity.



All silhouette dimensions are accurate at the listed ranges.

Subtensions



Ranging

MRAD measurements are effective for ranging using a simple formula. To use this formula, the shooter needs to know the size of the target or nearby object in yards, inches, meters, or cm.

$$\frac{\text{Target Size (yds.)}}{\text{Measured MRAD}} \times 1000 = \text{Range (yds.)}$$

$$\frac{\text{Target Size (inches)}}{\text{Measured MRAD}} \times 27.77 = \text{Range (yds.)}$$

$$\frac{\text{Target Size (inches)}}{\text{Measured MRAD}} \times 25.4 = \text{Range (m)}$$


$$\frac{\text{Target Size (m)}}{\text{Measured MRAD}} \times 1000 = \text{Range (m)}$$

$$\frac{\text{Target Size (cm)}}{\text{Measured MRAD}} \times 10 = \text{Range (m)}$$

For the most accurate solution, use the longest dimension. If the object is taller than it is wide, it is best to use the object's height in the formula.

Using either the vertical or horizontal MRAD scale, place the reticle on a target of known dimensions and read the number of MRAD spanned. You will obtain the best results if measured to the nearest 1/10 MRAD.

Accurate measuring will depend on a very steady hold. The optic should be firmly braced using a rest or a tripod. Once you have an accurate MRAD reading, use the formula to calculate the distance.




Ranging a 6' target (2 yds.) at 4 MRAD yields 500 yds.

$$\frac{2 \text{ yds.}}{4 \text{ MRAD}} \times 1000 = 500 \text{ yds.}$$

Quick Ranging with Silhouettes

The silhouettes used in the R/T Ranging reticle are based on an average 20" shoulder width and 11" head width. To use, simply match the object being ranged to the closest silhouette in shape and read the indicated yardage. You may also use other dimensions on the silhouette and compare to objects of known dimension to obtain range estimation.



ACCESSORIES

Utility Clip

The versatile Utility Clip allows quick attachment of the RECCE Pro® HD to MOLLE/PALS webbing, pocket edges, or other equipment.

Lanyard

The Lanyard can be worn around the neck or used as a safety cord when carrying it by the Utility Clip.

Attach the Lanyard in a few simple steps:



1. Detach the clip from the Lanyard.
2. Push the loop end through the Lanyard Attachment point on the monocular.
3. Pull the clip through the loop and cinch tight.
4. Re-attach the clip to the Lanyard.

Tethered Objective and Ocular Lens Caps

The RECCE Pro® HD has Tethered Objective and Ocular Lens Caps. The Ocular Lens Cap is designed to fit snugly inside the Winged Eyecup.

MOLLE/PALS Compatible Pouch

The RECCE Pro® HD comes with a pouch that may be attached to articles of gear or clothing using MOLLE/PALS straps.

Note: If the optic is exposed to moisture, keep the caps off and allow the optic to dry out completely before putting it in the case for storage.

MAINTENANCE

Cleaning

Your RECCE Pro® HD monocular requires very little routine maintenance other than periodically cleaning the exterior lenses. The exterior may be cleaned by wiping with a soft cloth. When cleaning the lenses, be sure to use products that are specifically designed for use on coated optical lenses.

- Be sure to blow away any dust or grit on the lenses prior to wiping the surfaces.
- Using your breath, or a very small amount of water or pure alcohol can help remove stubborn dried water spots.

Lubrication

All monocular components are permanently lubricated, so no additional lubricant should be applied.

Note: Do not attempt to disassemble any monocular components. Disassembling of the monocular may void warranty.

Storage

If possible, avoid storing your monocular in direct sunlight or any very hot location for long periods of time.

CAUTION: Monoculars are not intended for looking at the sun or other intense light sources. Such viewing could damage the retina and cornea of your eyes – even to the point of causing blindness.

NOTICE

Virtual Patent Marking Notice by Vortex Optics

This product may be protected by patents in the U.S. and elsewhere for Vortex Optics. <http://vtx.legal> website is provided to satisfy the virtual patent marking provisions of various jurisdictions including the virtual patent marking provisions of the America Invents Act and provide notice under 35 U.S.C. §287(a). Please visit <http://vtx.legal> to view list of products that may be covered by one or more U.S./Foreign patents or published patent applications.



VIP® WARRANTY

OUR UNCONDITIONAL PROMISE TO YOU.

We promise to repair or replace the product. Absolutely free.

- ▶ **Unlimited.**
- ▶ **Unconditional.**
- ▶ **Lifetime Warranty.**

You do not have to register, save the box, or a receipt for the Warranty to be honored.

Learn more at VortexOptics.com

service@VortexOptics.com • 1-800-4VORTEX

Note: The VIP® Warranty does not cover loss, theft, deliberate damage, or cosmetic damage not affecting product performance.

For the most up to date manual visit VortexOptics.com



M-00106-1

© 2025 Vortex Optics

® Registered Trademark and TM Trademark
are property of their respective owners.